A Study of Some Hydraulic Properties of technical Fabrics Used for Combat Desertification^{*}

Eng. Reem Salamon**

Dr. Eng. Taher Rajab Kaddar***

Dr. Eng M. Amin Tulemat****

Abstract

In this research, technical fabrics are used as blankets which prevent soil surface erosion and promote seed germination as way to mitigation of desertification.

Five different types of fabrics are prepared of natural fiber: coir, hemp, jute, treated cotton and raw cotton, then three hydraulic properties for prepared fabrics are tested: swell, water absorption, water vapour permeability.

It is found that all types of prepared fabrics are suitable to combat desertification whereas they have a high water absorption and they reduce water evaporation, the fabrics of jute and treated cotton have the highest water absorption and the fabrics of hemp and raw cotton have the lowest water vapour permeability.

Keyword: fabric used for combat desertification, swell, coir fabrics.

^{*}For the paper in Arabic see pages (449-456).

^{**} Ph.D. student at the Department of Textile and Spinning Engineering Faculty of Chemical and Petroleum Engineering

^{***}Department of Textile and Spinning EngineeringFaculty of Chemical and Petroleum Engineering

^{****} Department of Textile and Spinning EngineeringFaculty of Chemical and Petroleum Engineering

References:

- 1- A. R. Horrocks and S. C. Anand, Handbook of Technical Textiles, Woodhead Publishing, 2000
- 2- A technical guidance manual : terminology, index,& performance testing procedure for rolled erosion control blanket,Erosion Control Technology Council Copyright 2006
- 3- Amit Rawal, Harshvardhan Saraswat, Stabilisation of soil using hybrid needlepunched nonwoven geotextiles, Geotextiles and Geomembranes xxx (2010) 1-4
- 4- B P Saville, Physical testing of textile,1999 published by Woodhead Publishing Limited
- 5- Experimental Plot Design Meeting for TPN 3, DRAFT PROPOSAL PILOT PROJEC SAND DUNE FIXATION IN TPN 3 MEMBER COUNTRIEST, 29 April 2 May 2002
- 6- Gorman, J.M., J.C. Sencindiver, D.J. Horvath, R.N. Singh, and R.F. Keefer. 2000b. Erodibility of fly ash used as topsoil substitute in mineland reclamation. J. Env. Qual. 29: 805-811.
- 7- Irina Dinu, EROSION CONTROL PRODUCTS FROM SUGARCANE BAGASSE, B.S., AlexandruIoanCuza University, Iasi, Romania, 2000,December, 2006
- 8- Ismat M. El Hassan, Desertification Monitoring Using Remote Sensing Technology,2004, International Conf. on Water Resources & Arid Environment
- 9- Lyle, E.S. 1987. Surface mine reclamation manual. New York: Elsevier.
- 10- Meyer, L.D. 1985.Interrill erosion rates and sediments caracteristics. ASAE 29: 948-955
- 11- O.Ogbobe, K.S. Essien and A. Adebayo, ASTUDYOFBIODEGRADABLE GEOTEXTILES USED FOR EROSION

CONTROL, GEOSYNTHETICS INTERNATIONAL S 1998, VOL.5, NO.5 - المهندس خالد الشرع، التصحر وتدهور الأراضي في الجمهورية العربية السورية، المؤتمر الإقليمي حول قضايا تدهور الأراضي في المنطقة العربية، القاهرة، ٣٠٠٠ تشرين الأول / أكتوبر - ١٠ تشرين الثاني للجمهورية العربية السورية. / نوفمبر ٢٠٠٧، الورقة القطرية

- 13-http://www.alibaba.com/productfree/113866514/Jute_soil_saver_geo_jute.h tml
- 14-http://www.alibaba.com/product-free/110981732/Geo_Jute_Soil_Saver.html
- 15-<u>http://www.alibaba.com/product-tp/125225079/Hemp_woven.html</u>
- 16-<u>http://www.alibaba.com/productgs</u>
 /540030894/hemp_organic_cotton_men_s
 hirts .html
- 17-<u>http://www.alibaba.com/product</u>free/110256376/coir_net_geo_textile_ .html